



Haematocrit and Micro Tube Veterinary Centrifuges







Micro Tube Veterinary Centrifuge

FEATURES

- Compact, benchtop size
- Maintenance free drive
- Digital display
- Easy to use
- Displays RPM or RCF (g-force)
- Variable speed setting 500-15,000 RPM with count of 100 RPM
- Variable timer setting from 1 to 99 minutes and infinite mode
- One touch short spin feature
- · Lid lock and imbalance detection safety features

Use Together as a Combination



SPECIFICATIONS

Motor: Brushless DC Motor
Maximum Volume: 12 x 2ml (Micro Tube)
Speed Setting: 500 - 15,000 RPM

Maximum RCF: 15,596 x g
 Speed Accuracy: ± 100 RPM

Run Time: 1 - 99 minutes & infinite mode
 Acceleration Time: 60 ± 2 seconds

Deceleration Time: 50 ± 2 seconds

Weight: 50 ± 2 seconds

2.45kg approximate (with rotor)

• Dimensions: 2.43 kg approximate (with rotor)
• Dimensions: 190 x 120 x 270 mm (L x W x H)
• Electrical Requirements: 24V 23A

Electrical Requirements: 24V, 2.3A **Power Consumption:** 55W



Haematocrit Veterinary Centrifuge

FEATURES

- Compact, benchtop size
- Maintenance free drive
- Digital display
- Easy to use
- Preset for 12,000 RPM for 5 minutes
- Displays RPM and RCF (g-force)
- Variable speed setting 500-12,000 RPM
- Variable timer setting from 1 to 12 minutes
- Lid lock and imbalance detection safety features

SPECIFICATIONS

Motor: Brushless DC Motor

Maximum Volume: 24 x 40 / 75mm (Capillary Tubes)
 Speed Setting: 12,000 RPM

 Maximum RCF:
 14,119 x g

 Speed Accuracy:
 ± 100 RPM

Run Time:1 - 12 minutesAcceleration Time: 70 ± 5 secondsDeceleration Time: 80 ± 5 seconds

Weight: 5kg (without rotor)
 Dimensions: 301 x 365 x 105 mm (L x W x H)

Electrical Requirements: 24V, 6A
 Power Consumption: 135W



+44 (0) 1204 669033 (Option 1)



sales@woodleyequipment.com



www.woodleyequipment.com

 Old Station Park Buildings St. John Street Horwich Bolton Lancashire BL6 7NY

UK

"PASSIONATE ABOUT LABORATORY DIAGNOSTICS"

